





Virtual Tape Library

Product Specifications: LowEntry Standard

Model Name		VTL-2000 (Standard Config)	
		<u>VTL Appliance + 1-6 StorageUnits</u>	<u>Storage Expansion Unit</u>
Pictures			
Fibre Channel Interface	to Host Fabric	2-port @ 2Gbps FC each	
	to Disk Fabric	2-port @ 2Gbps FC each	
Specs per Disk Array	HDD-Size	250GB or 400GB SATA HDD	
	# of HDD	16	16
	Capacity	3.0TB or 4.8TB	3.0TB or 4.8TB
	RAID Specs	RAID5 2x (6DataDisks+1ParityDisk+1Spare)	
Compatible OS		Windows (NT/W2K), UNIX, Solaris, Linux, Netware	
Compatible Backup Software (Minimum Versions)		BakBone NetVault 5.0/6.5.3; CA BrightStor Enterprise Backup; CA ARCserve 2000; CA ARCserve Backup v9 for Windows; HP Omniback II / Data Protector; IBM Tivoli Storage Manager (TSM); Legato Networker 6.1x, 7.x; Veritas NetBackup DataCenter v4.5; Veritas Backup Exec. v8.6/9.0;	
EIA Units	VTL Appliance	1 unit	-
	Disk Array	1-6 units	1 unit
Size (HxWxD) mm	VTL Appliance	(2U) 88.6x483x670	-
	Disk Array	(3U) 132x482x500	(3U) 132x482x500
Weight (max) kg	VTL Appliance	12	-
	Disk Array	20	20
Power Requirement	Input Range	100 ~ 240 VAC	
	Frequency	50-60Hz	
	Plug	4x IEC320 C14	2x IEC320 C14
	Watt	2x 350 Watt 2x 460 Watt	2x 460 Watt redundant